

PI01

ABB Ability™ Symphony® Plus Hardware Selector



The PI01 pulse input module processes up to 8 Pulse Input signals. Each channel is individually CH-2-CH isolated and is independently configurable for Totalize, Frequency, Period or Duration mode pulse inputs. FC 221 (I/O Device Definition) sets PI module operating parameters and each input channel is configured using FC 229 (Pulse Input CH) to set individual input channel parameters such as pulse input mode, engineering units, High/Low alarm state, etc.

The PI01 module supports pulse counts from 0 to 16,777,215, frequency input range from 0.5 Hz to 100 kHz, and Period or Duration input ranges from 10 µsec to 30 seconds.

Features and benefits

- 8 individually CH-2-CH isolated Pulse Input channels supporting:
- Totalize: 0 to 16,777,215
- Frequency: 0.5 Hz to 100 kHz
- Period or Duration: 10 µsec to 30 seconds

| General info | |
|-----------------------------|-----------------------------------|
| Article number | PI01 |
| Type | Pulse Input |
| Life cycle status | ACTIVE |
| Number of channels | 8 |
| Signal type | PI |
| HART | No |
| SOE | No |
| Redundancy | No |
| Form factor | Standard (190 mm) |
| Mounting | Horizontal Row or Vertical Column |
| MTBF (per MIL-HDBK-217-FN2) | PR E: 338,368 Hours |
| MTTR (Hours) | 1 Hours |

| Detailed data | |
|---------------------------------|--|
| Module power requirements | 24 VDC ± 10%, 59 mA typical, 66 mA max |
| Module power connection | POWER TB on cHBX01L or VBX01T |
| Field IO power | 24 VDC ± 10%, 1.3 mA typical, 1.5 mA max per CH |
| Overvoltage category | Category I for power, inputs or outputs. Tested according to EN 61010-1 |
| Max field cable length | 600 meters (1968 feet) |
| Number of Channels | 8 Pulse Input Channels |
| Signal ranges and types | Pulse Inputs: 24 VDC |
| A/D Conversion | ±0 count |
| A/D Resolution | 0.0001 |
| A/D Update rate | 0.0001 |
| D/A Conversion | 0.0001 |
| Accuracy, FSR | Totalize: ±0 count Frequency: 0.01% Period: 0.01% Duration: 0.01% |
| Temp effect on accuracy | 0.015% @ 25°C (timebase accuracy) |
| Field signal to Logic isolation | Galvanically isolated, 1500 V up to 1 minute |
| Channel isolation | Individual CH-2-CH isolated, 1500 V up to 1 minute |

| Diagnostics | |
|---------------------|---|
| Front plate LED's | STATUS LEDs: R (Run) and F (Fault) + 1 thru 8 |
| Local availability | Mini USB connection on module front plate |
| Remote availability | HN800 device diagnostics via SPE |

| Environment and certification | |
|--|--|
| Temperature, Operating | -40 to +70 °C Tested according to IEC/EN 60068-2-1, IEC/EN 60068-2-2 |
| Temperature, Storage | -40 to +85 °C Tested according to MIL-STD-810G |
| Relative humidity | 20% to 95% @ 40°C non-condensing. Tested according to IEC/EN 60068-2-78, IEC/EN 61298-3 |
| Vibration (operational sinusoidal) | 5 to 60 Hz 0.137 mm (0.0054 in.), 60 to 150 Hz 1.0 G. Tested according to IEC/EN 60068-2-6 |
| Vibration (transportation) | 10 to 500 Hz. Tested according to MIL-STD-810G |
| Shock (storage) | 15 G, 11 msec. Tested according to IEC/EN 60068-2-27 |
| Drop | 100 mm. Tested according to IEC/EN 60068-2-31 |
| Protection class | IP20 according to EN 60529, IEC 529 |
| Altitude (operational) | Sea level to 3,048 meters (10,000 ft.) Tested according to MIL-STD-810G |
| Altitude (storage) | Sea level to 12,192 meters (40,000 ft.) Tested according to MIL-STD-810G |
| Air quality | ISA S71.04 G1, ISA S71.04 G3 compliant versions SPCxxxA are also available |
| ESD immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-2, Severity level 3 |
| Surge immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-5, Severity level 3 |
| Electrical fast transient immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-4, Severity level 3 |
| Radiated RFI immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-3, Severity level 3 |
| Conducted Immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-6, Severity level 3 |
| Magnetic field immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-8, Severity level 4 |
| Radiated emission | Tested accTested according to IEC/EN 61000-6-4, CISPR 11 + A1, CISPR 16-1-1, Group 1, Class A, ISM equipmentntording to IEC/EN 61000-6-2, IEC/EN 61000-4-6, Severity level 3 |
| Conducted emission | Tested according to IEC/EN 61000-6-4, CISPR 11 + A1, CISPR 16-1-1, Group 1, Class A, ISM equipment |
| Voltage dips and interruption immunity | Tested according to IEC/EN 61000-6-2, IEC/EN 61000-4-11 |
| CSA non-hazardous locations | Certified for use as process control equipment in an ordinary (non-hazardous) location |
| CSA hazardous, nonincendive locations | Class I, Division 2, Groups A, B, C, D |
| CE Mark | CE Mark EMC directive 2004/108/EC & Low Voltage Directive 2006/95/EC |
| RoHS compliance | RoHS Directive 2015/863 |
| WEEE compliance | DIRECTIVE/2012/19/EU |

| Compatibility | |
|-----------------------------|--|
| Use with MTU | HBS01-EPD, HBS01-FPH, HBS01-FPN, VBS01-EPD, VBS01-FPH, VBS01-FPN |
| Module keying code for base | slot #1 = 12, slot #2 = 17 |

| Dimensions | |
|------------|--------|
| Width | 27 mm |
| Depth | 106 mm |
| Height | 190 mm |
| Weight | 223 g |

solutions.abb/symphonyplus
solutions.abb/controlsystems

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved